



TR02-SM Robotic Seal Inserter

- Highly efficient rotary table to support up to 3 inserting robots and up to 3 seal feeders for each robot
- Yamaha robot with Keyence vision to deliver fast & accurate seal detection and insertion
- Support both soft seals and hard pins
- Full CNC control without any reforming dies required
- Powerful functions of graphic process setup & real time tracing, fast positioning, automatic rework, vision QC, scan input, data communications & production stats
- Quick interchangeable seal feeder, inserting head & housing fixture, automatic tooling match detection
- Optional material handler, pin cutter & MES interface



Specifications



Power	220-240VAC, 2.5KW standard
Compressed	Clean & filtered, ≥0.5kPa
Air	
Inserting Robot	Standard 1, optional 2-3
Seal Feeder	Standard 1/robot, optional 2-3/robots
Takt Time	60ppm(typical soft seal)
	24ppm (typical oriented hard pin)
Seal	Supports most types, clean edge, size
	tolerance, straightness and lubrication
	may be required
Vision System	Standard: QC check
	Optional: Pin orientation detection
Comms	Ethernet
Size & Weight	Main station: 800Dx800Wx1770H mm
	~350kg
	Feeder station:1000Dx800Wx1770H
	mm~550kg

Trivers Shanghai, established in 2007 by
Trivers Australia, has a series of over 10
products in robotic production lines & wire
harness assembly automation backed by
patents. It is an authorized supplier to
several Fortune 500 companies, is an
executive member of the Shanghai Robot
Alliance, and is a key member of
government R&D projects.

Contact Us

Trivers Automation Shanghai Pty Ltd

L11, Bld 13, 555 Chengyin Rd, Shanghai CHINA

Tel: 86-21-3638 6663
Fax: 86-21-5186 9166
Website: www.triverstech.cn

